

# S-Disk J

S-Disk J is a temperature data logger from -40°C to 250°C (standard calibration from 25°C to 140°C, calibrable from 0°C to 220°C, only the probe will resist above 140°C. For calibrations above 140°C probe minimum length is 50 mm) with 20 or 50 or 100 or 150 mm or on demand length external probe (probes cannot be switched) on a 13 mm cone base (base height is not counted for probe length), managed with Windows software and USB interface (DiskInterface HS, Multibay). **Battery is user replaceable** and the data logger is **provided with an Accredia (NIST equivalent) traceable certificate** on 6 points.

The other versions of the data logger are:

- S-Disk J Flexible: with flexible cable probe and rigid probe at the end
  - S-Disk J Bendable: with semi-rigid metal bendable probe and rigid probe at the end
  - S-Disk J Ultra Freeze: includes calibration points from -40°C for use also from -80°C
- There are also other models of high temperature data loggers, for pressure and humidity too.

Note: if used below -30°C, battery life will be highly reduced.

## Main features

- With different lengths rigid probe for penetration
- It is possible to request the calibration with ultra accuracy of  $\pm 0,05^{\circ}\text{C}$  in the range  $25^{\circ}\text{C} + 140^{\circ}\text{C}$
- Completely food grade and waterproof
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- Low battery consumption for an extended battery life
- User replaceable battery (**software shows battery status**)
- Very easy to deploy in any type of package
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from -40°C to 250°C** (order extra calibration points; in case of wide calibration range the accuracy might be worse. Request the possible calibration ranges in advance)

## Plus

- Extremely high accuracy and precision: with an accuracy of  $\pm 0,1^{\circ}\text{C}$  ( $\pm 0,05^{\circ}\text{C}$  with a special calibration) these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- High accuracy even outside the calibration range
- Fast response time thanks to the 3 mm diameter probe
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

## The system

The system is made up by:

- S-Disk J temperature data logger
- DiskInterface HS or Universal Multibay
- SPD software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)



## Applications



Sterilisation



Validation



Pharmaceutical



Healthcare



Medical



Laboratories



Food & Beverages



Pasteurisation

## Accessories

- SPD
- TS Manager
- DiskInterface HS
- Universal multibay
- Locking bolt
- Fastening system
- Teflon protective tube
- S-Disk J, L-Disk battery kit

## Technical specifications

Dimensions	29,5 h X 35 Ø (mm)
Weight	60 gr
Probe dimensions	Probe base dimensions 5 h X 14 Ø (mm) - Probe 20/50/100/150 l X 3 Ø (mm) - Probe l on demand X 3 Ø (mm) (l on demand: min. 10 mm / max. 175 mm. For longer probes ask for quotation)
Materials	Stainless steel AISI316L, PEEK
Temperature range	-40°C ÷ +140°C
Sensor temperature range	-40 °C ÷ +250 °C
Standard calibration points (temperature)	25/50/75/100/125/140°C
Extra calibration points (temperature)	Within the range -40 °C ÷ +250 °C
Temperature resolution	0,01 °C
Temperature accuracy	± 0,1 °C (within the calibration range) / ± 0,05 °C with ultra accuracy option
Memory (n. of acquisitions)	54.528
Acquisition step	From 1 every second up, with 1 second steps
Protection degree	IP68
Battery life	+8.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures)
Software&Mobile App	SPD, TS Manager
Accessories	DiskInterface HS, Multibay universale



**Tecnosoft srl**  
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy  
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875  
email: [info@tecnosoft.eu](mailto:info@tecnosoft.eu) - web: [www.tecnosoft.eu](http://www.tecnosoft.eu)  
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733

