

TempStick Probe -80

TempStick Probe -80 temperature data logger is a miniaturized temperature recorder with cable and rigid metal probe of various lengths, calibrated from -80°C up to 20°C; it has a wide range of monitoring applications especially in the food and pharmaceutical industry, for continuous monitoring in ultra freezers. Its reduced size and no need of external power supply make the TempStick system extremely versatile. The data logger can be supplied with calibration certificate with Accredia (Italian reference center, NIST equivalent) traceability.

The rigid metal probe is made with stainless steel AISI 316L, food grade, and is available in different types:

- 3 cm length, 4 mm diameter, rounded tip for immersion (ordering code 03)
- 8 cm length, 4 mm diameter, rounded tip for immersion (ordering code 04)
- 3 cm length, 4 mm diameter, pointed tip for penetration (ordering code 05)
- 8 cm length, 4 mm diameter, pointed tip for penetration (ordering code 06)

Cable is 2 mm diameter and has a standard length of 50 cm but it can be ordered longer.

Available also in the following versions:

- TempStick: with internal sensor
- TempStick Probe with handle: with cable, rigid probe, handle
- TempStick Probe: with cable, rigid probe
- TempStick Probe with thin cable: with thin cable, rigid probe
- TempStick Probe IP68: with cable, rigid probe, protected in an IP68 box
- TempStick Probe 200: with cable, rigid probe, for temperatures up to 200°C



Applications



Laboratories



Pharmaceutical



Healthcare



Medical



Food & Beverages



Industrial

Main features

- Mission programming and reading using a PC through the TecnoStick Interface or SRI and FLI portable interfaces
- Reduced size for easy use for every need
- Quick response time
- **Stand-by function:** start the logger and then, using the metallic clip, set it to a stand by status. In this way you can send many pre-programmed loggers to the sender of the products without providing him with the software and the interface. Before sending the goods he will just have to remove the clip to start the acquisitions
- Works with StickLog Pro and FridgeLog Z software

Plus

- High accuracy and precision
- Product's core temperature controlled directly
- Easy to use with SRI and FLI portable interfaces
- Compliant with HACCP and EN12830 regulations
- **MKT formula implemented**, for quick data analysis, also on SRI and FLI
- Provided with calibration certificate Accredia (NIST equivalent) traceable (on demand)
- Long life battery

The system

The basic system, for transport, is made up by:

- TempStick datalogger
- StickLog Pro software
- TecnoStick Interface or SRI

The FridgeLog Z system, for continuous monitoring, is made up by:

- TempStick datalogger
- FridgeLog Z software
- FLI interface

Accessories

- StickLog Pro
- TecnoStick Interface
- SRI
- FridgeLog Z
- FLI
- TempStick metal clip

Technical specifications

Dimensions	50 X 24 X 10 (mm)
Probe dimensions	Cable 500 l X 2 Ø (mm) or longer - Probe 30 or 80 l X 4 Ø (mm) pointed or rounded
Weight	36 gr
Temperature range	-30 °C ÷ +60 °C
Sensor temperature range	-80 °C ÷ +20 °C
Standard calibration points (temperature)	-80/-40/0/20°C
Extra calibration points (temperature)	Within standard calibration range
Temperature resolution	0,03 °C
Temperature accuracy	± 0,25 °C (within the calibration range) / ± 0,5 °C (within the range -80 °C ÷ -40 °C)
Memory (n. of acquisitions)	2.730
Acquisition step	From 1 every minute to 1 every 255 minutes
Battery life	Up to 10 years or 3 millions of acquisitions
Protection degree	IP63
Accessories	TecnoStick Interface, SRI, FLI



Tecnosoft srl
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875
email: info@tecnosoft.eu - web: www.tecnosoft.eu
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733

