

PressureDisk 05

PressureDisk 05 is a pressure data logger from 0 to 5 bar with 20 mm length external probe, managed with Windows software and USB interface (DiskInterface HS, Multibay).

Battery is user replaceable and the data logger is **provided with an Accredia (NIST equivalent) traceable certificate** on different points.

The other versions of the data logger are:

- PressureDisk: pressure and temperature data logger from -40 to a140°C and from 0 to 5 bar
 - PressureDisk V: pressure data logger for vacuum
- There are also other models of high temperature data loggers, for temperature only and humidity too.



Main features

- Resists up to 140°C
- Completely food grade and waterproof
- 1/2 Gass threaded connector to be screwed outside autoclave (the logger can still be used inside the autoclave though)
- **All software calculate lethality value (F0, PU, A0 ecc.)**
- Low battery consumption for an extended battery life
- User **replaceable battery (software shows battery status)**
- Accredia (NIST equivalent) traceable calibration certificate included
- Available **extended calibration from -40°C** (order extra calibration points)

Plus

- Extremely high accuracy and precision: these devices can be employed in any application involving pharmaceuticals, validation, laboratory and medical field
- Printed reports compliant with health regulations and ISO (data are not editable in the software)

The system

The system is made up by:

- PressureDisk temperature data logger
- DiskInterface HS or Universal Multibay
- HumiPressureDisk software or TS Manager software (compatible with the FDA 21 CFR Part 11 regulation)

Accessories

- HumiPressureDisk
- TS Manager
- DiskInterface HS
- Universal multibay
- PressureDisk battery kit

Applications



Validation



Sterilisation



Pharmaceutical



Medical



Healthcare



Laboratories



Food & Beverages

Technical specifications

Dimensions	43,22 h X 35 Ø (mm) - 55 (mm) total h with ½ Gass threaded part
Weight	145 gr
Materials	Stainless steel AISI316L, PEEK
Pressure range	0 bar ÷ 5 bar assoluti
Standard calibration points (pressure)	50/1k/2k/4k absolute mbar
Extra calibration points (pressure)	Within the range 10 mbar ÷ 5 bar
Pressure resolution	2 mbar
Pressure accuracy	± 15 mbar
Memory (n. of acquisitions)	27.264
Acquisition step	From 1 every second up
Protection degree	IP68
Battery life	+6.000.000 acquisitions at 1 second step continuously (calculated time @25°C. Battery life may be shorter if used in low temperatures)
Software&Mobile App	HumiPressureDisk, TS Manager
Accessories	DiskInterface HS, Multibay universale



Tecnosoft srl
Via Galvani, 4, 20068, Peschiera Borromeo (MI), Italy
T: (+39) 02 2692 2888 - F: (+39) 02 2692 2875
email: info@tecnosoft.eu - web: www.tecnosoft.eu
UNI EN ISO 9001:2008 Certiquality/IQNet N. 17733

